

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/047408 A1

(51) International Patent Classification⁷: **H04L 29/08**

(21) International Application Number:
PCT/IB2003/004800

(22) International Filing Date: 28 October 2003 (28.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02025751.5 15 November 2002 (15.11.2002) EP

(71) Applicant (for all designated States except US): **INTERNATIONAL BUSINESS MACHINES CORPORATION** [US/US]; New Orchard Road, Armonk, NJ 10504 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ROONEY, Sean** [IE/CH]; Uetlibergstrasse 42, CH-8045 Zurich (CH).

SCOTTON, Paolo [IT/CH]; Sennhuettenstrasse 37, CH-8810 Horgen (CH). **BAUER, Daniel** [CH/CH]; Alte Zuercherstrasse 43, CH-8903 Birmensdorf (CH). **WALDVOGEL, Marcel** [CH/CH]; Anton Graff-Strasse 15, CH-8400 Winterthur (CH).


(74) Agent: **TOLETI, Martin**; International Business Machines Corporation, Saeumerstrasse 4/Postfach, CH-8803 Rueschlikon (CH).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: **NETWORK TRAFFIC CONTROL IN PEER-TO-PEER ENVIRONMENTS**



(57) Abstract: A method and an electronic unit are disclosed for controlling traffic on a network, especially for controlling peer-to-peer related traffic. A filter unit is intercepting messages related to peer-to-peer application from a network line, irrespective of the messages' destination. A control logic then manages a request represented by an intercepted message subject to its content and subject to peering specific information.



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report

NETWORK TRAFFIC CONTROL IN PEER-TO-PEER ENVIRONMENTS**TECHNICAL FIELD**

5

The present invention relates to a network traffic control unit, a network comprising such a network traffic control unit, a method for controlling traffic on a network, and to a corresponding computer program product.

10

BACKGROUND OF THE INVENTION

Peer-to-peer applications become more and more popular since a wide range of data stored on computers on the edge of the Internet can now be accessed. Computers that stored and
15 provided data only for local access and in addition provided means for retrieving data from Internet servers may serve today as a data base for other computers and simultaneously may receive data not only from Internet servers but also from other remote computers when executing peer-to-peer applications. This widens the pool of accessible data tremendously.

20 Below, the term peer or node or peer node is used for an electronic device - for example a computer, a workstation or a PDA (personal digital assistant) but not limited to - that can run a peer-to-peer application. Therefore, such node should be able to access a network in order to exchange information with other nodes.

25 Gnutella is currently one of the most prominent representative of unstructured peer-to-peer applications, see "The Gnutella Protocol Specification v0.4 Document Revision 1.2", retrieved on the Internet http://www9.limewire.com/developer/gnutella_protocol_0.4.pdf and accessed November 15, 2002. These applications are called unstructured as nodes peer with other nodes in a random fashion. Searching in unstructured peer-to-peer network essentially is
30 a random probing as resources such as files or other services are made available on arbitrary nodes in the network, see "Search and Replication in Unstructured Peer-to-Peer Networks", Qin Lv et al., in 16th ACM International Conference on Supercomputing, June 2002. The

main advantages of these systems are their simplicity, for example the protocols used are very simple, and their dynamics in a sense that nodes can appear and disappear at a high rate. Another advantage is that search queries can be almost arbitrary complex and includes keyword-searching, substring-matching etc..

5

Peer-to-peer applications that include file exchange protocols - like Gnutella - Gnu V0.4 dynamically establish an "overlay" network to exchange information. When a peer is started, it tries to peer with other peers using a request/accept protocol. The requesting peer sends a "connect request" to another peer node. If this other peer authorizes the connection it answers
10 with a "connect accept" and the two parties establish a adjacency. Then they can start exchanging information that get passed on to other peers.

FIG. 1 illustrates the way connectivity is achieved within an exemplary network comprising at least two peer groups 1 and 2 - also called clusters. Each peer group 1 or 2 comprises peer
15 nodes A, B, C, respectively D and E. Reference 3 indicates some physical interconnection (wire-bound, wireless) between peer groups 1 and 2. Arrows indicate an already established peering connection which is rather a logical interconnection than a physical interconnection. Such connection is established by having one of the peers send a connect request message to the other peer and the other peer having accepted this connect request message with an accept
20 message according to the protocol of the peer-to-peer application.

In FIG. 1a), node C is peered with nodes A and B, as well as node D is peered with node E. Nodes C and D are prone to peering as C gets to know about D. Therefore C sends a connect request to D and D accepts by sending an accept message back to C.

25

According FIG. 1b), C and D are now peered and C relays messages to D, the messages issued by A and B, whereas D relays messages to C, the messages issued by E. In the following, A and D would like to peer as A gets to know about D. Therefore A sends a connect request to D and D accepts by sending an accept message back to A.

30

According to FIG. 1c), A and D are now peered in addition to the already existing peering connections. However, there are now two logical peering connections existing on the physical

interconnecting link 3. These two logical connections were established by means of at least four messages crossing the interconnection 3.

This overlay network - that is a term for the network of logical connections - is an ad-hoc
5 network that does not rely on an infrastructure. One well-known problem is how to bootstrap the peering mechanism, that is how a peer can find addresses of other peers to peer with. Usually two types of techniques are used to solve this problem. One solution consists of the peer connecting to a server located at a well-known address. This server maintains a list of peers' addresses that are communicated to the peer. Another solution is for the peer to
10 maintain itself a list of other peer it peered with and use addresses from this list.

In account of the technique, peering is done based on a list of addresses without taking into the actual network infrastructure or the affinity between peers. Therefore the resulting overlay network is typically totally de-correlated from the physical network. This can lead to a very
15 inefficient use of the network resources and poor performances of the file search protocol using this network.

Another example shown in Figure 2 demonstrates an example how a physical network is flooded with peer-to-peer application messages in order to establish adjacencies between peer
20 nodes. Three clusters 1, 2, 4 are shown. Big circles represent physical network nodes (e.g. routers, gateways), whereas small circles represent peer nodes. Dotted lines represent physical interconnections between physical network nodes, whereas straight lines represent logical interconnections between peer nodes. As can be derived from FIG. 2, peer node A is communicating with peer node F only via peer nodes B to E, while they are adjacent in the
25 physical network. Note that in this example links joining cluster 1 to cluster 2 and cluster 1 to cluster 3 will easily get congested.

Structure of peer-to-peer applications thus result in a limited scalability due to brute-force flooding and a clear misfit of the overlay network topology with the underlying Internet
30 topology representing the physical connections.

Flooding the underlying physical network with messages is not only a problem when looking for other peers to peer with but also when querying for information, such as data files, once an overlay network is established.

- 5 FIG. 3 introduces such exemplary query process according to the protocol of a peer-to-peer application: FIG. 3a) is similar to FIG. 1a) and shows the establishment of a peering connection between nodes C and D.

- According to FIG. 3b), node A now issues a query request "Looking for vivaldi.mp3". C
10 forwards this query request to B and D, D forwards this request to D. Arrows between two peer nodes pointing only in one direction indicate the transmitted query requests.

- E is supposed to have what A is looking for, so E sends a confirmation message to D, see FIG. 3c). D knows that the confirmation is related to a request coming from C so sends the
15 confirmation message to C. C knows that the confirmation message is related to a request coming from A so sends the confirmation message to A. Then, A contacts E using other means, e.g. HTTP, to get the file.

- EP 1 229 442 A2 discloses a peer-to-peer protocol that is meant to be uniform for many
20 different peer-to-peer applications. There are different layers defined, such as a platform core layer, a platform services layer, and a platform application layer. So-called rendezvous peers can maintain dynamic indexes for entities in the peer-to-peer platform including peers or peer groups. Rendezvous peers are considered to be peers executing additional functions.

- 25 "Identifying and Controlling P2P / File-Sharing Applications", retrieved from the Internet http://www.allot.com/html/solutions_notes_kazaa.shtml and accessed October 17, 2002, "Packeteer: Another take on limiting P2P traffic", by Ann Harrison, retrieved from the Internet <http://www.nwfusion.com/newsletters/fileshare/2002/01297785.html> and accessed October 17, 2002, "Four Steps to Application Performance across the Network", by
30 Packeteer/TM Inc., retrieved from the Internet <http://www.packeteer.de> and accessed October 17, 2002, each disclose a device that detects and identifies different types of traffic. In a

second step, network and application behaviour - especially bandwidth consumption - is analyzed. According to the analysis, bandwidth is allocated to different applications.

EP 1 075 112 A1 describes a PNNI hierarchical network, whereby one of the peers represents
5 a peer group as a peer group leader. The peer group leader has a memory for storing peer group topology data.

Several approaches to limit peer-to-peer traffic were introduced that are highly structured: "A
scalable Content-Addressable Network", by S. Ratnasamy et al., in ACM SIGCOMM, pages
10 161-172, August 2001; "Pastry: Scalable, decentralized object location and routing for large-scale peer-to-peer systems", by A. Rowstron and P. Druschel, in IFIP/ACM International Conference on Distributed Systems Platforms (Middleware), pages 329-350, November 2001; "Chord: A scalable Peer-to-peer Lookup Service for Internet Applications", by I. Stoica et al., in Proceedings of the 2001 ACM SIGCOMM Conference, pages 149-160,
15 August 2001. These approaches tightly control how and on which nodes information is stored. Also, peering of nodes is not random and the resulting overlay networks are often congruent to the underlying Internet topology. The disadvantage is that these approaches do not cope well with very high dynamics, i.e. a rapidly changing user population makes these systems unstable. Furthermore, these systems excel in exact-match queries but have some
20 weaknesses in key-word based queries and substring queries.

Therefore, it is desired to have network traffic controlling means provided while having peers causing such traffic remaining unchanged.

25

SUMMARY OF THE INVENTION

According to one aspect of the invention, there is provided a network traffic control unit, comprising a filter unit for intercepting messages from a network line. Messages are
30 intercepted relating to peer-to-peer application irrespective of the destination of a message. There is further provided a control logic that is configured for managing a request represented

by an intercepted message, subject to its content and subject to peering specific knowledge the network traffic control unit provides.

According to another aspect of the invention there is provided a method for controlling traffic
5 on a network, comprising receiving messages relating to peer-to-peer application, intercepted by a filter unit from a network line, irrespective of the messages' destination, and managing a request represented by an intercepted message, subject to its content and subject to peering specific information.

10 The filter unit filters messages that indicate in one way or another that they are peer-to-peer application related. Peer-to-peer applications typically enable user computers to act as both client and server for data files or services to other user computers. In a preferred embodiment, the filter unit is checking port fields of TCP messages with regard to appearance of defined port numbers in designated port fields that indicate peer-to-peer application. A peer-to-peer
15 application might use a port number to be identified that is different to the port number of other peer-to-peer applications, and different to port numbers of other non peer-to-peer applications. However, other significant information of a message might be used to filter peer-to-peer application related messages. The network traffic control unit and its filter unit might be prepared to filter and then to control only messages related to a certain peer-to-peer
20 application or might be prepared to filter and then to control messages of different known peer-to-peer applications. Messages not relating to a peer-to-peer application are typically not affected and can pass the filter unit unhamperedly.

The filter unit thus intercepts peer-to-peer application traffic on a network line irrespective of
25 the destination of the messages. The traffic that is filtered is thus not directed to the IP or whatever address of the network traffic control unit but typically addressed to peer destinations. Nevertheless, the network traffic control unit is intercepting this kind of traffic in order to get control on it.

30 In order to achieve extended control on peer-to-peer traffic on a network, it is considered to be preferred to give the network traffic control unit access to a network line that is carrying large amounts of such traffic. A preferred network line to be accessed by the filter unit is an

ingress/egress line to a group or cluster of peers, such that all or most of network traffic to or from peers of this clusters has to pass this network line and can be monitored.

On a lower level of a hierarchical communication layer, a message is represented by one or
5 more data packets as indicated above when talking about TCP protocol. Other protocols of course may be used instead. The filter unit might be embodied as packet filtering logic implemented on a network processor. Since the network traffic control unit and the associated proposed method have to primarily manage requests from peers, it is in particular appreciated to detect such requests. This detection can be implemented by the filter unit: For example, a
10 request might be expressed in the corresponding data packet with a defined code in a designated field of the data packet. Then, the filter unit can be prepared to check this field for a given number of codes representing a request. Other peer-to-peer application messages may also be filtered but treated differently from a management point of view than requests. Alternatively, messages comprising peer-to-peer application requests might be detected by
15 intercepting peer-to-peer application messages by means of the filter unit and having a command field of such messages analyzed by the control logic.

The control logic may be implemented in hardware or software or a combination thereof, or any other suitable implementation. A task that is assigned to the control logic is to manage
20 requests that are intercepted. Managing comprises, that such requests are now handled by the control logic in a way that might be different to the way the request pertaining peer-to-peer application envisages, but also satisfies the requesting peer, thereby preferably causing less traffic on the network than the peer-to-peer application would cause. The network traffic control unit therefore might preferably set up new messages, redirect requests, interact with
25 the requesting peer or peers intercepted messages are addressed to or even other network traffic control units. These are only some actions a network traffic control unit could provide, but not necessarily has to provide all of them. The opportunities for managing requests are on the other hand not limited to the enumerated actions.

30 Basically the control logic discovers the content of such intercepted message and coordinates measures to satisfy the needs expressed by such message dependent on the content of the message and dependent on knowledge the network control unit has, either stored in a memory

or by way of accessing other sources of knowledge. This knowledge is peering specific knowledge that helps in taking measures to satisfy queries, connect requests or other requests more efficiently. Typically, peers by themselves do not have this knowledge available.

- 5 Thus, the invention allows the dramatic reduction of network traffic caused by peer-to-peer applications by installing a network traffic control unit that takes the lead in managing requests intercepted from a network line. Adding such smart control creates benefits in controlling and limiting peer-to-peer application initiated traffic. This can be achieved without changing or amending neither participating peers nor the network structure and even without
- 10 making the introduction of such a network traffic control unit public with the peers or other entities within the network. The topology of the peer-to-peer overlay network is enhanced. Network control units can be added or removed without any requiring any changes to the peers.
- 15 The network traffic control unit can a stand alone electronic device in one preferred embodiment. In another preferred embodiment, the functions of the network traffic control are added to the functions of a router, such that only one device is responsible for both, router and traffic control functions.
- 20 According to many of the preferred embodiments introduced below, the control logic is sending messages in order to manage requests. This has to be interpreted such that the control logic primarily decides on sending messages, while the physical transmission of messages is initiated by an interface that is controlled by the control logic.
- 25 In a preferred embodiment, the intercepted message is dropped. This step is performed after having the content of the message evaluated. Dropping the intercepted message expresses that the control logic takes control for further managing and thinking about new ways to handle the request. This is a first traffic limiting effort.
- 30 Preferably, a request to be managed is a connect request issued from a peer node and directed to another peer node. Such connect request is sent in order to establish a connection to another peer, that may provide the contacting peer with the information or service the contacting peer

looks for after it accepted such connect request. It is important to have connect requests handled by the control logic of the network traffic control unit, since such connect requests might cause many other succeeding connect requests between other peers, for example when the peer-to-peer application determines to have a connected peer send connect requests to
5 other peers he is aware of. By managing such connect requests and thus controlling actions for satisfying these requests, the flood of peer-to-peer traffic can be contained dramatically.

A preferred way to manage a connect request is to handle further actions with regard to already existing connections the network traffic control unit is involved in. Whenever a peer is
10 requesting connectivity to a another peer, and the requesting peer is already connected to a third peer, preferably of the same remote cluster, the network traffic control unit might desist from sending a new request to this cluster, especially when it is aware that the other peer is already connected to the requesting peer via the third peer.

15 In a preferred embodiment, the network traffic control unit therefore provides peering specific knowledge information on peer-to-peer connections the network traffic control unit is currently aware of.

As indicated above, preferably no message might be sent to the addressee of the intercepted
20 connect request when a connection is already established that can serve the requesting peer node.

In another preferred embodiment, the control logic initiates sending a connect request to the originator of the intercepted connect request in response to the intercepted connect request.
25 This is to fully get control on the handling of the intercepted connect request. The network traffic control unit sends this connect request with its own ID as originator. In the following, the requesting peer exclusively communicates to the network traffic control unit. Traffic can be controlled and limited effectively.

30 Where appropriate, the network traffic control unit sends a connect request with its own ID as originator to the addressee of the intercepted connect request. This might be reasonable in order to satisfy the needs of the requesting peer as long as there is no other connection

established in particular to this peer or in general to this cluster. When there is a connection to another peer of this remote cluster, the network traffic control unit might prefer using the existing connection to reach the requested peer instead of fulfilling the original request to connect.

5

In another preferred embodiment, the network traffic control unit sends a connect request to the addressee of the intercepted connect request, thereby pretending the originator of the intercepted connect request is sending the connect request. This is an alternative method of controlling the establishment of connections, when the network traffic control unit is not
10 appearing under its own identity.

It may be preferred, sending a connect request to a peer node other than the addressee of the intercepted connect request in response to the intercepted connect request. This other peer node might support establishing a connection to the requesting peer node. There might be
15 different reasons and strategies, when a connect request is redirected by the network traffic control unit. Typically, the network traffic control unit acts under its own identity when redirecting a connect request.

Especially when a connect request is directed to a peer of another remote cluster and another
20 network traffic control unit is allocated to this cluster, it is preferred that the local network traffic control unit exclusively "talks" to peers of the other clusters via the remote network traffic control unit. This limits traffic drastically. Such a connect request to another network traffic control unit might also be advantageous in order to receive peering specific information the other network traffic control unit provides in preparation of connecting peers of the remote
25 cluster.

When the network traffic control unit is intercepting a connect request and acting in the following under its own identity, further actions might be preferably initiated only after the originator of the intercepted connect request accepts the connect request that is sent to him
30 from the network traffic control unit. This prevents generating traffic, when the originator is not prepared to communicate with the network traffic control unit.

Especially for managing connect requests described above, the network traffic control logic is preferably prepared to communicate according to a protocol of the peer-to-peer application.

Other requests that are preferably handled by the network traffic control unit are data file
5 queries issued by a peer node and brought to the attention of the network traffic control unit
by way of filtering. These query requests cause lots of succeeding traffic either, such that
effective management of handling such requests is vital for reducing overall peer-to-peer
induced traffic on the network. Typically, a query request is sent after peers are connected in
order to figure out which of these online peers can provide the information the querying peer
10 is looking for.

In a preferred embodiment, managing such a query request is subject to an index that allocates
keys representing data files for download or representing services to network traffic control
units. This index is considered as peering specific knowledge. A key specifies at least a part of
15 the content of a certain query and is generated from the content of the respective query request
according to fixed rules that the control logic preferably implements. Having such a key
derived from the query request, the network traffic control unit derives from this index, which
network traffic control unit among some or many network traffic control units is responsible
for administering information on this key. This information then maps peer nodes to keys. The
20 mapped peer nodes are currently registered for providing a file the key stands for.

In a preferred embodiment of the invention, the peering specific knowledge a network traffic
control unit provides comprises an index that allocates keys representing data files for
download to network traffic control units. This index is preferably locally stored in every
25 network traffic control unit and distributed regularly, respectively updated on a regular or
event driven basis. Every network traffic control unit is responsible for administering
information related to a number of keys. As keys in the end represent information on queries
and especially on queried data files, every network traffic control unit administers information
on a number of different data files. Such information, collected in another index then allocates
30 peer nodes to keys, giving thus detailed information which peer actually can provide a certain
data file.

Since looking for a file or a service can be expressed in queries in many different ways by different strings, the search strings of query requests are not very suitable for executing the query request immediately. Therefore, it is preferred, that one or more keys are derived from the content of the query request - that is particularly a string. The underlying set of rules is
5 preferably stored by the network traffic control unit; its control logic is configured for implementing such rules for deriving keys from query requests.

When such key or keys are derived from a query string by means of the control logic, and when a network traffic control unit that administers the keys is found by screening the
10 corresponding index, a request is directed to one or more remote network traffic control units that are allocated to the derived keys in order to obtain information which peers have the files represented by the keys available. The requested network traffic control unit or units preferably send such information back to the requesting network traffic control unit. A hit message from the network traffic control unit to the querying peer node might then be
15 preferred for having the peer node select any number of data files offered. Many preferred variations of this process are introduced later on.

Some network traffic control units therefore provide preferably a key - peer node index for some keys. These network traffic control units provide other network traffic control units with
20 the knowledge which peer nodes are allocated to a requested key according to the key - peer node index. Administration tasks of such a network traffic control unit preferably include updating the index by adding and removing entries.

In another preferred embodiment, a way of updating indexes of peering specific knowledge is
25 introduced: Hit messages sent from a peer node associated to the network traffic control unit are monitored. One or more keys are derived from the content of a hit message. The sending peer node is allocated to the derived keys, and the key - peer node relation is stored in the key - peer node index at the network traffic control unit that administers the index the key is part of. This method helps to keep peering specific knowledge up-to-date.

30

Preferably, such advanced search including underlying communication between network traffic control unit as well as administering indexes, tables or other peering specific

knowledge is accomplished using a protocol different to the peer-to-peer application protocol. Such protocol is more efficient and addresses the above mentioned purposes. This protocol is specifically used for managing query requests.

- 5 For many purposes, it is preferred to have peering specific knowledge available that comprises information on peer nodes associated to the network traffic control unit. This helps optimizing managing efforts as peer nodes of a joint cluster are typically located close to each other. Such distance information might affect managing requests by the network traffic control unit.
- 10 According to another aspect of the invention, there is provided a network comprising at least one group of peer nodes, a network line serving as ingress/egress line for this peer group, and a network traffic control unit according to any one of claims referring to such unit.

- According to another aspect of the invention, there is provided a computer program element
- 15 comprising computer program code which, when loaded in a processor unit of a network traffic control unit, configures the processor unit for performing a method as claimed in any one of the method claims.

- Advantages of the different aspects of the invention and their embodiments go along with the
- 20 advantages of the inventive network traffic control unit and method described above.

BRIEF DESCRIPTION OF THE DRAWINGS

- 25 The invention and its embodiments will be more fully appreciated by reference to the following detailed description of presently preferred but nonetheless illustrative embodiments in accordance with the present invention when taken in conjunction with the accompanying drawings.
- 30 The figures are illustrating:

FIG. 1, a known way of establishing peer-to-peer connections over a network,

FIG. 2, a symbolic diagram of a network showing connections established according to a known peer-to-peer application,

5 FIG. 3, a known way of querying information according to a known peer-to-peer application,

FIG. 4 a), a diagram showing a network, in accordance with an embodiment of the present invention,

FIG. 4 b), a block diagram of a network traffic control unit, in accordance with an

10 embodiment of the present invention,

FIG 4 c), a flow chart of a method for controlling traffic on a network, in accordance with an embodiment of the present invention,

FIG 5, a diagram showing the way messages are exchanged, in accordance with an

15 embodiment of the present invention,

FIG. 6, a way of establishing peer-to-peer connections over a network, in accordance with an embodiment of the present invention,

20 FIG. 7, another way of establishing peer-to-peer connections over a network, in accordance with an embodiment of the present invention,

FIG. 8, a symbolic diagram of a network showing connections established, in accordance with an embodiment of the present invention,

25

FIG. 9, a block diagram of a network, in accordance with an embodiment of the present invention,

FIG. 10, a data structure a network traffic control unit provides as peering specific knowledge,

30 in accordance with an embodiment of the present invention,

FIG. 11, a flow chart showing a search for data files or services, in accordance with an embodiment of the present invention, and

FIG. 12, a flow chart showing a method for updating peering specific knowledge.

5

Different figures may contain identical references, representing elements with similar or uniform content.

10 DETAILED DESCRIPTION OF THE DRAWINGS

FIG. 4 shows embodiments of different aspects of the present invention. FIG. 4a) illustrates a chart of a network in accordance with an embodiment of the present invention, FIG. 4 b) a block diagram of a network traffic control unit in accordance with an embodiment of the present invention, and FIG 4 c) a flow chart of a method of controlling traffic in accordance with an embodiment of the present invention.

FIG. 4 a) shows two clusters 1 and 2. The clusters 1 and 2 are physically connected via an interconnection 3. Cluster 1 comprises some routers 10 and an edge router 11 being the router that is directly connected to the interconnection line 3 - also called network line 3. Neither are shown the peers belonging to each clusters nor any logical connections between peers.

A network traffic control unit 5 - also called booster - is introduced in the network co-located with the network ingress/egress node - that is the edge router 11 -, in order to control at least a large part of the traffic the cluster 1 is transmitting and receiving. This traffic is present on the network line 3.

FIG. 4b) shows a block diagram of the network traffic control unit 5. The network traffic control unit 5 comprises a filter unit 51, being implemented in a network processor. The filter unit 51 is monitoring the network line 3 and filters all messages on this network line 3 that relate to peer-to-peer applications. Other messages - respectively the corresponding data packets - are not affected and take their way to destination on network line 3. The network

traffic control unit 5 further comprises a control logic 52 that receives intercepted messages and also has capability to send respectively initiate sending messages over the network line 3. A memory 53 is provided for storing peering specific knowledge the control logic has access to.

5

FIG. 4 c) shows a flow chart of the way the network traffic control unit 5 is having impact on messages that are sent the over network line 3, and especially to messages that represent a connect request sent from a peer of cluster 1. Overall principle here is controlling the establishment of the overlay network topology by the network traffic control unit 5 and

10 thereby enhancing the performances of the protocol.

The basic principle is to intercept peer-to-peer connect requests issued by cluster 1 peers and to force the requesting peer to peer with the network traffic control unit 5. The interception is performed by the filter unit 51. Only the network traffic control unit 5 peers with external peers
15 and if necessary relays protocol message issued by the peers located inside the network cluster 1. Whenever control logic 52 takes the decision that according to the content of the intercepted request - that might be the request from peer X to connect to peer Y - and according to peering specific knowledge - that might be the information, that peer X is already connected to peer Y via another peer of the same cluster - the intercepted packet is dropped
20 and no further action is required. This drastically limits the traffic on the ingress/egress link and allows the protocol to scale.

FIG. 5 shows the protocol exchanges leading to the interception of the connect request and how the booster peers with the requested peer. Peer A sends a connect request to peer B.

25

Booster 5 intercepts since a peer-to-peer application message is detected. Originators address, addressee, and content of the message - that is a connect request - are extracted. Then the connect request is dropped. Booster 5 then issues a connect request under its own identity to the peer A who is going to accept it as it is looking for peer nodes.

30

The booster 5 then might peer with external peers or other boosters. This scheme can be extended using sophisticated information exchanges among boosters to enhance the protocol's

performances. For example, summaries of files available in the booster's network can be generated using distributed hash tables (e.g. CAN/Chord or Pastry/Tapestry).

FIG. 6 shows a diagram explaining the way messages are exchanged in accordance with an embodiment of the present invention. It is illustrated how connectivity is achieved within an exemplary network comprising at least two peer groups 1 and 2. Each peer group 1 and 2 comprises peer nodes A, B, C, respectively D and E. Reference 3 indicates a network line between peer groups 1 and 2. Arrows pointing in two directions indicate an already established peering connection which is rather a logical interconnection based on some physical interconnection. Such connection is established by having one of the peers sent a connect request message to the other peer and the other peer having accepted this connect request message with an accept message according to the protocol of the peer-to-peer application.

In FIG. 6a), node C is already peered with nodes A and B, as well as node D is peered with node E. Nodes C and D are prone to peering as C gets to know about D. Therefore C sends a connect request to D. Such messages are indicated by an arrow pointing from the originator to the addressee. In the charts, only the originator of a message is indicated verbally in brackets. But the real message also contains the identification of the addressee.

20

A network traffic control unit 5 according to an embodiment of the invention is introduced. The identifier of the network traffic control unit 5 is "G". It filters messages of peer-to-peer applications. Thus, the connect request from C to D is intercepted by the network traffic control unit 5. Its information/content is extracted and the request is dropped. Now, network traffic control unit 5 takes full control on managing further actions in response to the intercepted connect request to fulfill the needs of C: It therefore sends a connect request to C. C accepts. According to peering specific knowledge the network traffic control unit 5 has access to, it is still necessary to contact D. Therefore, network traffic control unit 5 sends a connect request to D containing its identifier G. D accepts.

30

According to FIG. 6b), C and G are peered now as well as G and D are. Now A and D would like to peer as A gets to know about D. Therefore A sends a connect request to D that is

intercepted by G = network traffic control unit 5. The request is dropped after extracting the message's content. G sends a connect request to A. A accepts.

There is no need for establishing a further logical connection between A and D since C is
5 already connected to D and A is connected to C. Thus, the network traffic control unit 5 takes no further action and in particular does not send the connect request from A further or contacts D another time. According to FIG. 6c), there is no further connection between A and D, or G and D as a result. Thus, traffic is limited.

10 FIG. 7 shows basically an alternative to FIG. 5 with regard to the way messages are exchanged. FIG. 7 illustrates the same network with the same elements as FIG. 6. The way the network traffic control unit 5 manages intercepted connect requests is now different: The network traffic control unit 5 does not appear under its own identity but manipulates in a more hidden way. Connect requests are still intercepted and dropped. After having evaluated
15 peering specific knowledge and the content of the message, it might still be reasonable for network traffic control unit 5 to contact D. But now, D is approached with a connect requests that looks like the original one sent by C, showing C as originator instead of G. The accept message from D is also intercepted and an identical accept message is forwarded to C by the network traffic control unit 5. This method is shown in FIG. 7a). FIG 7 b) illustrates the actual
20 connections of the overlay network afterwards.

FIG. 8 illustrates a diagram of a network as an embodiment of the invention. Compared to the known network according to FIG. 2, now network traffic control units 5 are installed at ingress/egress nodes. They are exclusively responsible for establishing the overlay network
25 which is indicated by straight lines. As can be derived from the diagram, there is only one connection between network traffic control units 5 of different clusters 1, 2, 4 established which reduces traffic tremendously. Also, peer A can now peer with peer F via peer B within cluster 1. This knowledge was provided and applied by the network traffic control units 5 while establishing connections and managing intercepted connect requests.

30

The scalability problems of unstructured peer-to-peer approaches can alternatively or in addition to be alleviated by replacing the brute-force searching (querying) with an intelligent

data location mechanism. Thus, the network traffic control unit provides managing capabilities for managing query requests that are intercepted and analyzed. Again, the peers can remain unchanged whereas in the core of the network an advanced location mechanism is used. FIG. 9 shows a network according to an embodiment of the invention. The peers that are
5 located within three peer groups 1, 2 and 4 are all named as Gnutella Peers, as in this embodiment the traffic related to Gnutella peer-to-peer application should be managed. The network traffic control units 5 are located such that each network traffic control unit 5 is associated with a peer group such that a network traffic control unit 5 has access to all sent or received messages the peers of his group are involved in when communicating to peers of
10 other peer groups. With regard to physical network topology, network traffic control units typically sit between access and edge routers such that they may intercept peer-to-peer messages. Like this, a network traffic control unit serves a number of peers in its vicinity to which it is network close.

15 Among the network traffic control units 5 and especially for managing intercepted query requests in an intelligent low-traffic way, a protocol different to the peer-to-peer protocol is used in order to better match these new requirements. Such protocol may be named "Advanced Search and Location Protocol". The advantages of this approach are: In the core of the network, flooding is replaced by a scalable advanced location mechanism. This improves
20 scalability and significantly reduces the amount of control traffic. The peers do not have to be replaced or changed. In particular, a highly dynamic peer population is supported. The network traffic control units 5 are relatively stable and thus fulfill the requirements of structured peer-to-peer systems. They protect the network from flooding messages and use an advanced location mechanism instead.

25

In the following, the architecture is explained using the Gnutella protocol as an example for a peer-to-peer application protocol. Other unstructured peer-to-peer approaches work similarly. The peers execute the Gnutella protocol to locate files and execute HTTP to download files. Network traffic control units also implement the Gnutella protocol in order to communicate
30 with the peers. Unlike standard peers, network traffic control units do not participate in flooding Gnutella requests. Between network traffic control units, an advanced location mechanism is used.

A part of the control logic managing capabilities is preferably the application of a set of rules for translating the content of queries - and especially the strings of such queries representing the content - into keys. Keys are more easy to query and less vague in representing a statement
5 than language is. In addition, keys are more short than strings and therefore need less bandwidth.

A given input string is first processed by a stop-word filter that removes all words that are insignificant for the search. A parser then generates a set of hash-codes - that are regarded as
10 special implementation of keys using hash-functions - from the remaining words of the query. In the most simple case, the parser generates a single hash-code from each word. A sophisticated parser maps content to a hierarchical structure, for instance

```
15      filetype = "music"
      format = "mp3"
      artist = "vivaldi"
      conductor = "karajan"
```

and allocates a key to this structure.

20

For each valid sub string of a query, additional keys might be computed. This allows to implement sub string queries. Details of how this could be achieved are described in "A Scalable Peer-to-Peer Architecture for Intentional Resource Discovery" by Magdalena Balazinska, et al., Pervasive 2002 - International Conference on Pervasive Computing, August
25 2002, which is hereby incorporated by reference.

The resulting keys are used to retrieve information from a distributed key - peer index. The key - peer index is distributed among network traffic control units in a way that every network traffic control unit maintains only a part of the overall key - peer index. A single network
30 traffic control unit is administering a limited number of keys. Such key - peer index maps peers that store the file the key is related to.

FIG. 10 illustrates data structure of such a key - peer index stored on a single network traffic control unit. The network traffic control unit keeps a fraction of the overall distributed key - peer index. A given key maps to none, one or more filenames and the corresponding file is stored on one or several peers.

5

Basic logic of managing queries that is implemented in the control logic of a network traffic control unit includes preferably:

For a given key, the control logic locates the network traffic control unit on which more
10 information associated with this key are stored. There is preferably an index or a function available mapping keys to network traffic control units. A key and its associated information - especially peer and filename, and possibly the network traffic control unit that is associated to the peer - might be stored on multiple network traffic control units. In this case, the control logic locates the one which is closest to the requesting network traffic control unit. The key -
15 network traffic control unit index is dynamic in the sense that new network traffic control units can be added and existing ones can be removed. Compared to the change rate of the peers, the change rate of the network traffic control units is expected two of magnitude lower.

The result of a key query is a list of filenames which are then returned to the peer that
20 originally issued the query. Optionally these filenames may be compared by the network traffic control unit against the filenames extracted from the original query in order to produce a ranking list, which is then returned to the peer. Also, due to the inherent nature of generating keys and especially hashing there is always a non-null chance of two different inputs being mapped into the same key. This also might cause preference to double check, e.g. by way of
25 comparing original filename and returned filename.

FIG. 11 illustrates a flow chart of managing a query request triggered by a peer that sends a query message 100. The network traffic control unit might be a peer and therefore receives the message or alternatively intercepts the message by diverting peer-to-peer traffic - here
30 Gnutella traffic - from the network.

The network traffic control unit then proceeds as follows:

It computes a set of hash codes 103 based on the search string. For each valid sub string, a hash code is computed, too. This allows to implement sub string queries. Stop-word filter and name parser techniques are applied for generating the hash-codes, step 101, 102. These steps
5 can of course have different order.

The network traffic control unit locates the destinations in terms of other network traffic control units where the derived hash-codes / keys are administered. This is achieved by means of a key - network traffic control unit index. A query message for the computed keys is sent
10 from the managing network traffic control unit to the discovered remote network traffic control units. Upon reception of such message, the remote network traffic control unit will return values associated with the queried key, step 104. These values comprise of a list of Peers that store the requested file. For each peer, the associated network traffic control unit is also listed.

15

Whenever the specific keys are stored on the managing network traffic control unit, there is of course no need for contacting other network traffic control units and the peers that are associated to the queried keys can be detected on the local network traffic control unit.

20 The returned keys might be translated into strings and be compared to the original query string sent by the requesting peer, step 105.

If the list is not empty, then the managing network traffic control unit returns a hit message to the querying peer and gives itself as source, step 106. A peer might then be free to chose
25 among the returned filenames and select any number of them for retrieval.

If either a push request or a HTTP get request arrives at the network traffic control unit, then the network traffic control unit selects the real data source - i.e. a specific peer - to retrieve the file from. As selection criteria it may use the quality of the network connection (delay,
30 throughput, error rate, or other parameters that might be evaluated by the network traffic control units) and freshness of information. The network connection for retrieving is not offered to the offering peer but instead to its associated network traffic control unit, as the two

network traffic control units are assumed to be correlated. In locality-aware DHT's, evaluation of the network connection is delivered without any additional overhead.

After the serving peer is chosen, the managing network traffic control unit starts retrieving
5 the file from this peer via the associated network traffic control unit, then directly forwarding it to the querying peer.

In case an entry is not available - that might mean the peer that was listed as offering a file has disappeared or no longer has this file - an explicit removal procedure as described below is
10 executed to disseminate this new information to the other network traffic control units. Also, the managing network traffic control unit may decide to retrieve from another - for example the next best - offering peer instead, or directly notifying the querying peer of the failed attempt.

15 FIG. 12 depicts a flow chart for an insert operation that is based on monitoring hit messages that are forwarded through the network. The insert method is managed by the control logic of an network traffic control unit.

As soon as a network traffic control unit observes a hit answer according to the peer-to-peer
20 application protocol that originates from one of its local peers a new entry in the distributed key - peer index has to be performed as follows:

The network traffic control unit computes a set of keys, step 201, 202 based on the filename 200. This computation is analogous to the one used for the search operation. For each key that
25 is computed, the managing control logic identifies a network traffic control unit that is administering this key. If that key is not existing yet, it is assigned to one of the network traffic control units. The administering network traffic control units then stores the key together with the filename, the address of the peer as well as the IP address of the associated network traffic control unit.

30

A remove operation that also updates the key - peer index can include of an implicit and / or explicit part. Implicit removals occur if an index entry wasn't accessed for some time. Time

outs are expected to be in the range of one or more hours. Implicit removals are done by each network traffic control unit individually by periodically checking entries that have timed out. Explicit removals occur when a download from an index entry did not succeed either because the file or the peer has disappeared. In this case, the index entry is removed on all network

5 traffic control units that store the associated key.

CLAIMS

- 5 1. Network traffic control unit, comprising
- a filter unit (51) for intercepting messages
 - relating to peer-to-peer application,
 - from a network line (3),
 - irrespective of destination,
- 10 • a control logic (52) that is configured for managing a request represented by an intercepted message subject to its content and subject to peering specific knowledge the network traffic control unit (5) provides.
2. Network traffic control unit according to claim 1,
- 15 wherein the network traffic control unit (5) is prepared to communicate according to a peer-to-peer application protocol.
3. Network traffic control unit according to claim 2,
- wherein the network traffic control unit (5) is prepared to apply the peer-to-peer application
- 20 protocol for managing connect requests.
4. Network traffic control unit according to any one of the claims 1 to 3,
- wherein the network traffic control unit (5) is prepared to communicate according to a protocol different to the peer-to-peer application protocol.
- 25
5. Network traffic control unit according to claim 4,
- wherein the network traffic control unit (5) is prepared to apply the protocol different to the peer-to-peer application protocol for managing query requests.
- 30 6. Network traffic control unit according to any one of the preceding claims,
- wherein the peering specific knowledge comprises information on peer-to-peer connections the network traffic control unit (5) is currently aware of.

7. Network traffic control unit according to any one of the preceding claims,
wherein the peering specific knowledge comprises information on peer nodes associated to the
network traffic control unit (5).

5

8. Network traffic control unit according to any one of the preceding claims,
wherein the peering specific knowledge comprises an index that allocates keys representing
data files for download to network traffic control units.

10 9. Network traffic control unit according to any one of the preceding claims,
wherein the peering specific knowledge comprises an index that allocates peer nodes to keys
representing data files for download.

10. Network traffic control unit according to any one of the preceding claims,
15 wherein the control logic (53) is configured for implementing a set of rules for deriving keys
from intercepted query requests.

11. Method for controlling traffic on a network, comprising:

- receiving messages related to peer-to-peer application, intercepted by a filter unit from a
20 network line (3), irrespective of the messages' destination,
- managing a request represented by an intercepted message subject to its content and
subject to peering specific information.

12. Method according to claim 11, comprising
25 dropping the intercepted message.

13. Method according to claim 11 or claim 12,
wherein a request to be managed is a connect request issued from a peer node and directed to
another peer node.

30

14. Method according to claim 13,

wherein managing the connect request is subject to existing connections the network traffic control unit is aware of.

15. Method according to claim 14,

- 5 wherein no message is sent to the addressee of the intercepted connect request when a connection is already established that can serve or be extended to serve the requesting peer node.

16. Method according to any one of the claims 13 to 15, comprising

- 10 sending a connect request to the originator of the intercepted connect request in response to the intercepted connect request.

17. Method according to one of the claims 13, 14 or 16, comprising

sending a connect request to the addressee of the intercepted connect request.

15

18. Method according to one of the claims 13, 14 or 16, comprising

sending a connect request to the addressee of the intercepted connect request pretending the originator of the intercepted connect request is sending the connect request.

- 20 19. Method according to one of the claims 13 to 16, comprising

sending a connect request to a peer node other than the addressee of the intercepted connect request.

20. Method according to one of the claims 13 to 16, comprising

- 25 sending a connect request to another network traffic control unit (5).

21. Method according to claim 16 in combination with any one of the claims 17 to 20,

sending the connect request to another party than the originator of the intercepted connect request once the originator has accepted the connect request from the network traffic control

- 30 unit directed to the originator.

22. Method according to any one of the preceding claims 11 to 21,

wherein a request to be managed is a data file query issued by a peer node.

23. Method according to claim 22,

wherein managing the query request is subject to an index that allocates keys representing data

5 files for download to network traffic control units.

24. Method according to claim 22 or claim 23,

wherein managing the query request is subject to an index that allocates peer nodes to keys.

10 25. Method according to any one of the claims 22 to 24, comprising

deriving one or more keys from the content of the query request.

26. Method according to claim 25, comprising

directing a request to one or more remote network traffic control units that are allocated to the

15 derived keys according to the key - network traffic control unit index.

27. Method according to claim 26, comprising

receiving a list of peer nodes that are allocated to the keys, from the remote network traffic control unit.

20

28. Method according to claim 27, comprising

sending a hit message to the querying peer node.

29. Method according to any one of the preceding claims 11 to 28, comprising

- 25 • administering a key - peer node index for some keys, and
- providing other network traffic control units on request with the knowledge which peer nodes are allocated to a requested key according to the key - peer node index.

30. Method according to claim 29,

30 wherein administering the key - peer node index comprises removals of entries.

31. Method according to any one of the preceding claims 11 to 30, comprising

- monitoring hit messages sent from an associated peer node,
- deriving one or more keys from the content of a hit message,
- allocating the sending peer node to the derived keys, and
- storing the key - peer node relation in a key - peer node index.

5

32. A network comprising

- at least one group (1, 2, 4) of peer nodes,
 - a network line (3) serving as ingress/egress line for this peer group (1, 2, 4), and
 - a network traffic control unit (5) according to any one of the preceding claims 1 to 10,
- 10 intercepting messages from the network line.

33. A computer program element comprising computer program code which, when loaded in a processor unit of a network traffic control unit, configures the processor unit for performing a method as claimed in any one of claims 11 to 31.

15





Fig. 1

**Fig. 2**

3/9




Fig. 3

4/9




Fig. 4

5/9




Fig. 5




Fig. 8

6/9




Fig. 6




Fig. 7

8/9




Fig. 9




Fig. 10

9/9




Fig. 11




Fig. 12

INTERNATIONAL SEARCH REPORT

Inter...ication No
PC...03/04800

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04L29/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC, IBM-TDB

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2002/107982 A1 (BJORNER NIKOLAJ S ET AL) 8 August 2002 (2002-08-08)	1-7, 11-22, 32, 33 8-10, 23-31
Y	paragraph '0016! paragraphs '0029!, '0030! paragraphs '0035!-'0037! paragraph '0046! paragraphs '0070!-'0087! paragraph '0123!	
Y	US 6 442 571 B1 (HAFF MAURICE W ET AL) 27 August 2002 (2002-08-27) column 6, line 1-7 column 7, line 52 -column 8, line 8 column 9, line 45-62 column 11, line 19-57	8-10, 23-31
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

4 February 2004

Date of mailing of the international search report

11/02/2004

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Hes, R

INTERNATIONAL SEARCH REPORT

inter
PC 3/04800 plication No

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 2002/147810 A1 (ABDELAZIZ MOHAMED M ET AL) 10 October 2002 (2002-10-10)</p> <p>abstract</p> <p>paragraphs '0027!-'0030!</p> <p>paragraphs '0282!-'0293!</p> <p>paragraph '0405!</p> <p>paragraphs '0412!, '0413!</p> <p>-----</p>	1-33

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. Classification No.

PCT/US 03/04800

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2002107982 A1	08-08-2002	WO 02058360 A2	25-07-2002
		AU 3526302 A	03-06-2002
		AU 3526402 A	03-06-2002
		EP 1338133 A2	27-08-2003
		WO 0242900 A2	30-05-2002
		WO 0242901 A2	30-05-2002
		US 2002062336 A1	23-05-2002
		US 2002062375 A1	23-05-2002
US 6442571 B1	27-08-2002	US 6219669 B1	17-04-2001
		US 2002184224 A1	05-12-2002
		AU 757557 B2	27-02-2003
		AU 1460599 A	07-06-1999
		BR 9815290 A	04-12-2001
		CA 2309660 A1	27-05-1999
		EA 2886 B1	31-10-2002
		EP 1038368 A2	27-09-2000
		JP 2002506246 T	26-02-2002
		WO 9926121 A2	27-05-1999
US 2002147810 A1	10-10-2002	US 2002156893 A1	24-10-2002
		US 2003041141 A1	27-02-2003
		EP 1229442 A2	07-08-2002
		EP 1229443 A2	07-08-2002
		WO 02057917 A2	25-07-2002
		US 2002143944 A1	03-10-2002
		US 2002143855 A1	03-10-2002
		US 2002184310 A1	05-12-2002
		US 2002184357 A1	05-12-2002
		US 2002184311 A1	05-12-2002
		US 2003002521 A1	02-01-2003
		US 2002152299 A1	17-10-2002
		US 2002184358 A1	05-12-2002
		US 2002188657 A1	12-12-2002
		US 2002147771 A1	10-10-2002
		EP 1282289 A2	05-02-2003
		US 2003028585 A1	06-02-2003
		US 2003070070 A1	10-04-2003
		US 2003055894 A1	20-03-2003
		US 2003055898 A1	20-03-2003